


JB-750 flexible, colour coded, 750 V, meter marking



HELUKABEL JB-750 5G2,5 QMM / 11166 450/750 V 001041419

CC



Technical data

- Special-PVC control cable adapted to DIN VDE 0285-525-2-11 / DIN EN 50525-2-11 and IEC 60227-5
- **Temperature range**
flexing -15°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage**
U₀/U 450/750 V
fixed installation, under protection
U₀/U 600/1000 V
- **Test voltage** 4000 V
- **Breakdown voltage** min. 8000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Minimum bending radius**
flexing 7,5x cable Ø
fixed installation 4x cable Ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper-conductor, to DIN VDE 0295 cl.5, fine-wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of special PVC compound type T12 to DIN VDE 0207-363-3 / DIN EN 50363-3
- Core identification to JB/OB colour code
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay-length
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1/DIN EN 50363-4-1
- Sheath colour grey (RAL 7001)
- with meter marking

Properties

- Extensively oil resistant, oil-/chemical resistance see table Technical Informations
 - The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers
- Tests**
- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)

Note

- G = with green-yellow conductor
x = without green-yellow conductor (OB).
- Cleanroom qualification tested with analog type. Please note "cleanroom qualified" when ordering.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- screened analogue type:
Y-CY-JB

Application

These cables are used for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms but not suitable for open air, as measuring and control cables in tool machinery, conveyor belts, production lines, as well as in machinery production, in air-conditioning and steel production plants. The earth core is located immediately below the outer sheath. JB cables are suitable for use in all electrical equipment either in dry or damp areas. They should not, however, be installed in the open air.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11161	2 x 2,5	8,6	48,0	130,0	14
11162	3 G 2,5	9,3	72,0	164,0	14
11163	3 x 2,5	9,3	72,0	164,0	14
11164	4 G 2,5	10,2	96,0	200,0	14
11165	4 x 2,5	10,2	96,0	200,0	14
11166	5 G 2,5	11,4	120,0	247,0	14
11167	5 x 2,5	11,4	120,0	247,0	14
11168	6 G 2,5	12,6	144,0	301,0	14
11169	7 G 2,5	12,6	168,0	321,0	14
11121	2 x 4	10,6	76,8	195,0	12
11144	3 G 4	11,3	115,0	235,0	12
11122	4 G 4	12,5	154,0	295,0	12
11123	5 G 4	13,9	192,0	361,0	12
11124	7 G 4	15,4	269,0	498,0	12
11125	11 G 4	20,2	422,0	767,0	12
11126	3 G 6	12,8	173,0	355,0	10
11127	4 G 6	14,2	230,0	424,0	10
11128	5 G 6	15,8	288,0	525,0	10
11129	7 G 6	17,4	403,0	625,0	10
11153	3 G 10	16,2	290,0	611,0	8
11130	4 G 10	18,1	384,0	701,0	8
11131	5 G 10	20,1	480,0	858,0	8
11132	7 G 10	22,2	672,0	1106,0	8
11154	3 G 16	19,8	461,0	912,0	6
11133	4 G 16	22,0	614,0	1035,0	6
11134	5 G 16	24,4	768,0	1259,0	6
11135	7 G 16	27,0	1075,0	1780,0	6

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11155	3 G 25	24,4	720,0	1388,0	4
11136	4 G 25	27,1	960,0	1581,0	4
11137	5 G 25	30,1	1200,0	1997,0	4
11156	3 G 35	27,0	1008,0	1767,0	2
11138	4 G 35	29,9	1344,0	2105,0	2
11139	5 G 35	33,4	1680,0	2636,0	2
11157	3 G 50	31,9	1440,0	2556,0	1
11140	4 G 50	35,5	1920,0	2940,0	1
11145	5 G 50	39,2	2400,0	3936,0	1
11158	3 G 70	36,4	2016,0	3182,0	2/0
11141	4 G 70	40,2	2688,0	4090,0	2/0
11146	5 G 70	44,9	3360,0	5443,0	2/0
11159	3 G 95	41,5	2736,0	4676,0	3/0
11142	4 G 95	46,0	3648,0	5540,0	3/0
11147	5 G 95	51,3	4560,0	6931,0	3/0
11160	3 G 120	45,9	3456,0	5630,0	4/0
11143	4 G 120	51,3	4608,0	7000,0	4/0
11148	4 G 150	58,7	5760,0	8340,0	300 kcmil
11149	4 G 185	64,3	7104,0	9904,0	350 kcmil

Dimensions and specifications may be changed without prior notice. (RA01)